
















# DB Schenker U.S.A.

## Ocean Container Specs

Standard Containers	Door Opening	Interior Length	Interior Width	Interior Height	Weight Capacity	Use
 <b>20' Box</b>	W: 7'8" 2.34m H: 7'6" 2.28m	19'4" 5.89m	7'8" 2.34m	7'10" 2.38m	Tare Weight: 4,916 lbs 2,229 kg. Cubic Capacity: 1,158 cu. ft. 32.80 cbm Payload: 47,999 lbs 21,727 kg.	General goods
 <b>40' Box</b>	W: 7'8" 2.34m H: 7'6" 2.28m	39'5" 12.01m	7'8" 2.34m	7'10" 2.38m	Tare Weight: 8,160 lbs 3,701 kg. Cubic Capacity: 2,362 cu. ft. 66.89 cbm Payload: 59,040 lbs 26,780 kg.	General goods
 <b>40' High Cube</b>	W: 7'8" 2.34m H: 8'5" 2.56m	39'5" 12.01m	7'8" 2.34m	8'10" 2.69m	Tare Weight: 8,750 lbs 3,968 kg. Cubic Capacity: 2,670 cu. ft. 75.60 cbm Payload: 58,450 lbs 26,512 kg.	General goods
 <b>45' High Cube</b>	W: 7'8" 2.34m H: 8'5" 2.56m	44'6" 13.58m	7'8" 2.34m	8'10" 2.69m	Tare Weight: 9,061 lbs 4,110 kg. Cubic Capacity: 3,019 cu. ft. 85.48 cbm Payload: 62,589 lbs 28,390 kg.	Voluminous and light cargo
Reefer Containers	Door Opening	Interior Length	Interior Width	Interior Height	Weight Capacity	Use
 <b>20' Reefer</b>	W: 7'5" 2.26m H: 7'3" 2.20m	17'8" 5.38m	7'5" 2.26m	7'5" 2.26m	Tare Weight: 7,040 lbs 3,193 kg. Cubic Capacity: 970 cu. ft. 27.48 cbm Payload: 45,760 lbs 20,756 kg.	Goods requiring a constant temperature above/below freezing point; controlled fresh air supply
 <b>40' Reefer</b>	W: 7'5" 2.26m H: 7'3" 2.20m	37'11" 11.56m	7'5" 2.26m	7'5" 2.26m	Tare Weight: 10,780 lbs 4,889 kg. Cubic Capacity: 2,085 cu. ft. 59.04 cbm Payload: 56,276 lbs 25,526 kg.	Goods requiring a constant temperature above/below freezing point; controlled fresh air supply
 <b>40' Reefer High Cube</b>	W: 7'5" 2.26m H: 8'2" 2.50m	37'11" 11.56m	7'5" 2.26m	8'2" 2.49m	Tare Weight: 9,524 lbs 4,320 kg. Cubic Capacity: 2,297 cu. ft. 65.05 cbm Payload: 62,126 lbs 28,180 kg.	Goods requiring a constant temperature above/below freezing point; controlled fresh air supply

Metric	US Conversions	Metric	US Conversions	US	Metric Conversions	US	Metric Conversions
1 cm	0.3937 inches	1,000 kg	1.102 short tons	1 inch	2.54 cm	1 short ton	908 kg
1 m	3.281 feet	1 cm <sup>2</sup>	0.061 cu-inches	1 foot	0.305 m	1 cu-inch	16.3873 cm <sup>2</sup>
1 m	1.094 yards	1 m <sup>2</sup>	35.3134 cu-feet	1 yard	0.914 m	1 cu-foot	0.0283 m <sup>2</sup>
1 g	0.0353 ounces	1 m <sup>2</sup>	1.3079 cu-yards	1 ounce	28.35 g	1 cu-yard	0.765 m <sup>2</sup>
1 kg	2.205 pounds	1 km	0.621373 miles	1 pound	0.4536 kg	1 mile	1.60934 km



Specialized Containers	Door Opening	Interior Length	Interior Width	Interior Height	Weight Capacity	Use
 <b>20' Open Top</b>	Removable Door Header	19'4" 5.89m	7'7" 2.31m	7'8" 2.34m	Tare Weight: 5,280 lbs 2,394 kg. Cubic Capacity: 1,124 cu. ft. 31.84 cbm Payload: 47,620 lbs 21,600 kg.	Overheight goods, loading from above/side possible
 <b>40' Open Top</b>	Removable Door Header	39'5" 12.01m	7'7" 2.31m	7'8" 2.34m	Tare Weight: 8,490 lbs 3,850 kg. Cubic Capacity: 2,293 cu. ft. 64.92 cbm Payload: 58,710 lbs 26,630 kg.	Overheight goods, loading from above/side possible
 <b>20' Flat Rack</b>		18'5" 5.61m	7'3" 2.20m	7'4" 2.23m	Tare Weight: 5,578 lbs 2,530 kg. Payload: 47,333 lbs 21,469 kg.	Heavy and extra-wide goods
 <b>40' Flat Rack</b>		39'7" 12.06m	7'3" 2.20m	7'4" 2.23m	Tare Weight: 12,081 lbs 5,479 kg. Payload: 85,800 lbs 38,918 kg.	Heavy and extra-wide goods
 <b>40' Collapsible Flat Rack</b>		39'7" 12.06m	7'3" 2.20m	7'4" 2.23m	Tare Weight: 12,783 lbs 5,798 kg. Payload: 66,397 lbs 30,117 kg.	Heavy and extra-wide goods
 <b>20'/40' Platform</b>		19'11" 6.07m  40' 12.19m	8'0" 2.43m  8' 2.43m		Tare Weight: 12,783 lbs 5,798 kg. Payload: 66,397 lbs 30,117 kg.  Tare Weight: 12,783 lbs 5,798 kg. Payload: 66,397 lbs 30,117 kg.	Heavy and extra-wide goods
 <b>20' Ventilated</b>	W: 7'6" 2.29m H: 7'5" 2.28m	19'7" 5.94m	7'3" 2.21m	7'9" 2.38m	Payload: 48,215 lbs 21,870 kg.	For goods requiring ventilation
 <b>20' Bulk</b>	W: 7'8" 2.34m H: 7'5" 2.27m	19'4" 5.89m	7'9" 2.36m	7'8" 2.35m	Tare Weight: 5,622 lbs 2,550 kg. Cubic Capacity: 1,151 cu. ft. 32.6 cbm Payload: 47,289 lbs 21,450 kg.	For dry bulk goods

All dimensions referenced represent common internal & external dimensions and may vary depending upon the carrier and equipment availability. Please contact your local DB Schenker office to verify specific equipment size before booking your shipment.